


1N5400G~1N5408G

3.0Amp Glass Passivated Standard Rectifiers

Features

- The plastic package carries Underwriters Laboratory Flammability Classification 94V-0
- Glass Passivated Junction chip
- Low reverse leakage
- High forward surge current capability
- High temperature soldering guaranteed
250°C/10 seconds at terminals

DO-27



Dimensions in inches and (millimeters)

Mechanical Data

- Case** : Molded plastic body
- Terminals** : Solder plated, solderable per MIL-STD-750, Method 2026
- Polarity** : Polarity symbol marking on body
- Mounting Position** : Any
- Weight** : 0.0345 ounce, 0.98 grams

Maximum Ratings And Electrical Characteristics

Ratings at 25°C ambient temperature unless otherwise specified. Single phase half-wave 60Hz, resistive or inductive load, for capacitive load current derate by 20%.

Parameter	SYMBOLS	1N	1N	1N	1N	1N	1N	1N	1N	1N	UNITS
		5400G	5401G	5402G	5403G	5404G	5405G	5406G	5407G	5408G	
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	200	300	400	500	600	800	1000	V
Maximum RMS voltage	V _{RMS}	35	70	140	210	280	350	420	560	700	V
Maximum DC blocking voltage	V _{DC}	50	100	200	300	400	500	600	800	1000	V
Maximum average forward rectified current at T _L =100°C	I _(AV)	3.0									A
Peak forward surge current, 8.3ms single half sine-wave superimposed on rated load	I _{FSM}	150.0									A
Maximum instantaneous forward voltage at 3.0A	V _F	1.10									V
Maximum DC reverse current T _A =25°C at rated DC blocking voltage T _A =125°C	I _R	5.0 500									uA
Typical junction capacitance (Note1)	C _J	50.0									pF
Typical thermal resistance	R _{qJA}	45.0									°C/W
Operating junction and storage temperature range	T _J , T _{STG}	-55 to +150									°C

Note: 1. Measured at 1MHz and applied reverse voltage of 4.0V D.C.

1N5400G~1N5408G

3.0Amp Glass Passivated Standard Rectifiers

Ratings And Characteristic Curves

FIG. 1- DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PER LEG




FIG. 3-TYPICAL FORWARD VOLTAGE CHARACTERISTICS




FIG. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS

